

N542 SPI RF Module

SI4432 FSK RF Module,410 to 960Mhz

INTRODUCTION

N542 is a low-cost and small size Lora RF module for transmitting and receiving digital data via radio frequency. All of the N542's electronics (don't including an antenna) reside on a single PCB, and all operational power is derived from a single supply voltage.

The transceiver design consists of a SI4432 low-power, integrated sub 1G transceiver RF chip,all IO pin are brought out.The module available frequency is from 410 to 960Mhz,The hardware is designed for maximum range.The visual distance up to 2000m.

Technical specifications

Hardware Information

Interfaces: IO
Dimension: 16 x 16mm x 3mm
Operating voltage: 2 - 3.6V
Operating temperature: -30°C to +80°C

Consumption(Sleep) : 1uA
Consumption (RX): 18mA
Consumption (TX): 120mA
RF chip: SI4432
Mounting: SMD

Software

Asynchronous Transparent mode
Low Power mode
Secure mode


RSSI mode
Serial bootloader
Adjustable packet size

Wireless Interface


RF pin
Frequency:410-510Mhz,860-960Mhz
Modulation: FSK
RF deviation: ± 10 Khz

RF data rate: 1.2 - 500kbps
RF output power: up to 20dBm
RF sensitivity: -120dBm

Pin configuration & Dimensions



PIN define



PCB LAYOUT(mm)

Part numbers

N542-A-S-434M RF Module N542-A-S-434M – 100mW – 410-510Mhz

OTHER MODULES OF BANDS RANGE

N542-A-S-868M RF Module N542-A-S-868M – 100mW – 860-960Mhz

Manufacturer

SHENZHEN NANCHENG TECHNOLOGY CO.,LTD

Contact with us

Shenzhen NanCheng Technology CO.,LTD
Addr: Room307,Xinbaoyuan Building,N5179,District 74 Xinan Street,
BaoAn District,Shenzhen,China 518101
Sales department: +0086 755 29662101
E-mail : info@hkulike.com
Web: www.hkulike.com