



Brochures of Zigbee

Zigbee Product

Contact information: **Shenzhen HeYan Technology CO.,LTD**
Hongkong Ulike Electronic Co.,Ltd
Address:Room307,Xinbaoyuan Building,N5179,District 74 Xin'an Street, BaoAn
District,Shenzhen,China 518101
Sales department: +0086 755 29662101
E-mail : info@hkulike.com
Web: www.hkulike.com

Zigbee RF Product



N700AS

RF data rate: 250 kbps
RF output power: + 4dBm
RF sensitivity: - 96 dBm
Modulation: DSSS,Zigbee
Frequency: 2405MHz to 2480MHz
PCB antenna
Interfaces: SPI,UART,IIC
Dimension: 26 x 15 x 3 mm
Operating voltage: 2-3.6V
Consumption (Sleep): 1uA
RF chip: TI CC2530
Mounting: SMD



N702AS

RF data rate: 250 kbps
RF output power: + 20dBm
RF sensitivity: - 100 dBm
Modulation: DSSS,Zigbee
Frequency: 2405MHz to 2480MHz
PCB antenna,IPEX
Interfaces: SPI,UART,IIC
Dimension: 33 x 19 x 3 mm
Operating voltage: 2-3.6V
Consumption (Sleep): 1uA
RF chip: TI CC2530
Mounting: SMD



N703AP

RF data rate: 250 kbps
RF output power: + 4dBm
RF sensitivity: - 100 dBm
Modulation: DSSS,Zigbee
Frequency: 2405MHz to 2480MHz
PCB antenna
Interfaces: SPI,UART,IIC
Dimension: 28 x 18 x 3 mm
Operating voltage: 2-3.6V
Consumption (Sleep): 1uA
RF chip: TI CC2630
Mounting: SMD



N709AP

RF data rate: 250 kbps
RF output power: + 20dBm
RF sensitivity: - 100 dBm
Modulation: DSSS,Zigbee
Frequency: 2405MHz to 2480MHz
PCB antenna,ipex
Interfaces: USB
Dimension: 60 x 18 x 3 mm
Operating voltage: 5V
RF chip: TI CC2531
Mounting: USB PLUS



N707AP

RF data rate: 250 kbps
RF output power: + 4dBm
RF sensitivity: - 96 dBm
Modulation: DSSS,Zigbee
Frequency: 2405MHz to 2480MHz
PCB antenna
Interfaces: USB
Dimension: 34 x 17 x 3 mm
Operating voltage: 5V
RF chip: TI CC2531
Mounting: USB PLUS



N710AP

RF data rate: 250 kbps
RF output power: + 21dBm
RF sensitivity: - 100 dBm
Modulation: DSSS,Zigbee
Frequency: 2405MHz to 2480MHz
PCB antenna,ipex
Interfaces: USB
Dimension: 60 x 18 x 3 mm
Operating voltage: 5V
RF chip: TI CC2538
Mounting: USB PLUS



N706AP

RF data rate: 250 kbps
RF output power: + 4dBm
RF sensitivity: - 96 dBm
Modulation: DSSS,Zigbee
Frequency: 2405MHz to 2480MHz
PCB antenna
Interfaces: USB
Dimension: 46 x 17 x 3 mm
Operating voltage: 5V
RF chip: TI CC2531
Mounting: USB PLUS



N711AP

RF data rate: 250 kbps
RF output power: + 4dBm
RF sensitivity: - 98 dBm
Modulation: DSSS,Zigbee
Frequency: 2405MHz to 2480MHz
PCB antenna,ipex
Interfaces: USB
Dimension: 50 x 18 x 3 mm
Operating voltage: 5V
RF chip: TI CC2538
Mounting: USB PLUS



N713AP

RF data rate: 250 kbps
RF output power: + 4dBm
RF sensitivity: - 96 dBm
Modulation: DSSS,Zigbee
Frequency: 2405MHz to 2480MHz
PCB antenna
Interfaces: USB
Dimension: 43 x 18 x 3 mm
Operating voltage: 5V
RF chip: TI CC2530,CP2102
Mounting: USB PLUS



N714AP

RF data rate: 250 kbps
RF output power: + 20dBm
RF sensitivity: - 100 dBm
Modulation: DSSS,Zigbee
Frequency: 2405MHz to 2480MHz
PCB antenna,ipex
Interfaces: USB
Dimension: 53 x 18 x 3 mm
Operating voltage: 5V
RF chip: TI CC2530,CC2592,CP2102
Mounting: USB PLUS



For questions please contact with us!

Contact information: **Shenzhen HeYan Technology CO.,LTD**
Hongkong Ulike Electronic Co.,Ltd
Address:Room307,Xinbaoyuan Building,N5179,District 74 Xin an Street, BaoAn
District,Shenz hen,China 518101
Sales department: +0086 755 29662101
E-mail : info@hkulike.com
Web: www.hkulike.com

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.