



Real time transmission RF Product

Contact information: **Shenzhen HeYan Technology CO.,LTD**
Hongkong Ulike Electronic Co.,Ltd
Address:Room307,Xinbaoyuan Building,N5179,District 74 Xin'an Street, BaoAn
District,Shenzhen,China 518101
Sales department: +0086 755 29662101
E-mail : info@hkulike.com
Web: www.hkulike.com

Real Time Transmission RF Product



N501AS

RF data rate: 1 - 300 kbps
 RF output power: +12dBm
 RF sensitivity: -116 dBm
 Modulation: GFSK, FSK
 Frequency: 862MHz to 928MHz
 (Option:431Mhz to 464Mhz)
 RF pin
 Interfaces: SPI,UART,IIC
 Dimension: 29 x 21 x3 mm
 Operating voltage: 2-3.6V
 Consumption (Sleep): 1uA
 Chip: ADF7023,MCU
 Mounting: SMD



N502AS

RF data rate: 1 - 300 kbps
 RF output power: +24dBm
 RF sensitivity: -122 dBm
 Modulation: GFSK, FSK
 Frequency: 862MHz to 928MHz
 (Option:431Mhz to 464Mhz)
 RF pin
 Interfaces: SPI,UART,IIC
 Dimension: 36 x 24 x 3 mm
 Operating voltage: 2-3.6V
 PA Operating voltage: 3-5V
 Consumption (Sleep): 1uA
 Chip: ADF7023,MCU
 Mounting: SMD



N502ES

RF data rate: 1 - 300 kbps
 RF output power: +30dBm(3.6V)
 RF sensitivity: -124 dBm
 Modulation: GFSK, FSK
 Frequency: 862MHz to 928MHz
 (Option:431Mhz to 464Mhz)
 RF pin,IPEX
 Interfaces: SPI,UART,IIC
 Dimension: 42 x 24 x 3 mm
 Operating voltage: 2-3.6V
 PA Operating voltage: 2-5V
 Consumption (Sleep): 2uA
 Chip: ADF7023,MCU
 Mounting: SMD




N502FS

RF data rate: 1 - 300 kbps
 RF output power: +33dBm (5V)
 RF sensitivity: -124 dBm
 Modulation: GFSK, FSK
 Frequency: 862MHz to 928MHz
 RF pin,IPEX
 Interfaces: SPI,UART,IIC
 Dimension: 42 x 24 x 3 mm
 Operating voltage: 2-3.6V
 PA Operating voltage: 3-5V
 Consumption (Sleep): 2uA
 Chip: ADF7023,MCU
 Mounting: SMD



N210AS

RF data rate: 50 to 2000 kbps
 RF output power: + 3dBm
 RF sensitivity: -96 dBm
 Modulation: FSK
 Frequency: 2400MHz to 2483MHz
 PCB antenna,IPEX
 Interfaces: SPI,UART,IIC
 Dimension: 32 x 21 x 3 mm
 Operating voltage: 3V Consumption
 (Sleep): 1uA
 RF chip: Semtech ADF7242
 Mounting: SMD



N211AS

RF data rate: 50 to 2000 kbps
 RF output power: + 20dBm
 RF sensitivity: -96 dBm
 Modulation: FSK
 Frequency: 2400MHz to 2483MHz
 PCB antenna,IPEX
 Interfaces: SPI,UART,IIC
 Dimension: 38 x 24 x 3 mm
 Operating voltage: 3V
 Consumption (Sleep): 1uA
 RF chip: Semtech ADF7242
 Mounting: SMD



For questions please contact with us!

Contact information: **Shenzhen HeYan Technology CO.,LTD**
Hongkong Ulike Electronic Co.,Ltd
Address:Room307,Xinbaoyuan Building,N5179,District 74 Xin an Street, BaoAn
District,Shenz hen,China 518101
Sales department: +0086 755 29662101
E-mail : info@hkulike.com
Web: www.hkulike.com

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.