

N538BP, CC1312R+PA Dongle



N538BP dongle Introduce

N538BP CC1312R1F3RGZ transceiver dongle designed for 169M, 433M, 868M, 915MHz and 1200Mhz band. Up to +24 dBm output power and down to -110 dBm sensitivity at 50 kbps.

N538BP is a low-cost and small size FSK RF transceiver dongle for transmitting and receiving digital data via radio frequency. All of the N538BP's electronics (don't including an antenna) reside on a single PCB.

The transceiver dongle based TI wireless MCU CC1312R1F3RGZ and PA, CC1312R1 integrated sub 1G transceiver RF chip. The dongle available frequence is from 160 to 960Mhz and 1200Mhz. The hardware is designed for maximum range, 1000m + Range (Line of Sight, 50 kbps).

N538BP dongle integrated TI CC1312R1F3RGZ, PA, TCXO, spring antenna, LED, key, and UART TO USB chip.

N538BP dongle supports Multiple protocols, eg: Wi-Sun and WMbus. AT command supports.

N538BP is suitable for ISM band in China, EU and USA.

N538BP Dongle Parameter

Model	N538BP	
dongle Interface	USB 2.0	
Frequency	169M, 433M, 868M, 915MHz and 1200Mhz	
RF Data Rate	1.2-4000 kbps	
Transmitting Power	+24 dBm	
Receiving Sensitivity	-110 dBm at 50 kbps	



TX Current	300 mA		
RX Current	21 mA		
Frequency Deviation	+/- 1 khz		
Communication Distance	10 – 1000 m(Visual distance)		
Antenna Interface	IPEX, spring antenna		
Installation Mode	USB PLUG		
Volume (mm)	37 mm x 17 mm x 7 mm		
Operating Voltage	+ 5 V		
Working Temperature and Humidity	Temperature: -40 - 80 ℃; Humidity 10-95 %RH		
Environment			
Storage Temperature and Humidity	Temperature: -40 - 80 ℃; Humidity 10-95 %RH		
Environment			
Weight (kg)	≈10g		

Application Area

Ultra low-power wireless applications

Operating in the 868/915 MHz ISM/SRD bands

Wireless alarm and security systems

Industrial monitoring and control

Wireless sensor networks

AMR - Automatic Meter Reading

Home and building automation

Wireless MBUS

Arduino

Ordering Information

N538BP-CC1312R1F3RGZ-169M	RF dongle	CC1312R1F3RGZ+PA	200mW – 160-175Mhz
N538BP-CC1312R1F3RGZ-433M	RF dongle	CC1312R1F3RGZ+PA	200mW – 410-510Mhz
N538BP-CC1312R1F3RGZ-868M	RF dongle	CC1312R1F3RGZ+PA	200mW - 860-960Mhz
N538BP-CC1312R1F3RGZ-1200M	RF dongle	CC1312R1F3RGZ+PA	200mW – 1200-1250Mhz



More information please contact with us.