

# N538EP, CC1314R10+PA Dongle



#### **N538EP dongle Introduce**

N538EP CC1314R10 transceiver dongle designed for 169M, 433M, 868M, 915MHz and 1200Mhz band. Up to +24 dBm output power and down to -110 dBm sensitivity at 50 kbps.

N538EP is a low-cost and small size FSK RF transceiver dongle for transmitting and receiving digital data via radio frequency. All of the N538EP's electronics (don't including an antenna) reside on a single PCB.

The transceiver dongle based TI wireless MCU CC1314R10 and PA, CC1314R10 integrated sub 1G transceiver RF chip. The dongle available frequence is from 160 to 960Mhz and 1200Mhz. The hardware is designed for maximum range, 1000m + Range (Line of Sight, 50 kbps).

N538EP dongle integrated TI CC1314R10, PA, TCXO, spring antenna, LED, key, and UART TO USB chip. N538EP dongle supports Multiple protocols, eg: Wi-Sun and WMbus. AT command supports.

N538EP is suitable for ISM band in China, EU and USA.

#### **N538EP Dongle Parameter**

Model	N538EP	
dongle Interface	USB 2.0	
Frequency	169M, 433M, 868M, 915MHz and 1200Mhz	
RF Data Rate	1.2-4000 kbps	
Transmitting Power	+24 dBm	
Receiving Sensitivity	-110 dBm at 50 kbps	



TX Current	300 mA	
RX Current	21 mA	
Frequency Deviation	+/- 1 khz	
Communication Distance	10 – 1000 m(Visual distance)	
Antenna Interface	IPEX, spring antenna	
Installation Mode	USB PLUG	
Volume (mm)	37 mm x 17 mm x 7 mm	
Operating Voltage	+ 5 V	
Working Temperature and Humidity	Temperature: -40 - 80 ℃; Humidity 10-95 %RH	
Environment		
Storage Temperature and Humidity	Temperature: -40 - 80 ℃; Humidity 10-95 %RH	
Environment		
Weight (kg)	≈10g	

## **Application Area**

Ultra low-power wireless applications

Operating in the 868/915 MHz ISM/SRD bands

Wireless alarm and security systems

Industrial monitoring and control

Wireless sensor networks

AMR - Automatic Meter Reading

Home and building automation

Wireless MBUS

Arduino

### **Ordering Information**

N538EP-CC1314R10-169M	RF dongle	CC1314R10+PA	200mW – 160-175Mhz
N538EP-CC1314R10-433M	RF dongle	CC1314R10+PA	200mW – 410-510Mhz
N538EP-CC1314R10-868M	RF dongle	CC1314R10+PA	200mW - 860-960Mhz
N538EP-CC1314R10-1200M	RF dongle	CC1314R10+PA	200mW – 1200-1250Mhz



More information please contact with us.